



Aluminum Zirconium alloy AlZr10

1. Properties & Application:

Zirconium content: 8~12%. Used for the Zr element additive or grain refining of aluminum alloys in the course of smelting. Using temperature low, low wastage of Zr element.

2. Operation Technology Suggestion:

(1). Temperature: 720℃ minimum.

(2). Dosage: according to calculating and experimental results.

(3). Method: heating to the appropriate temperature, skim off the dross and put AlZr10 into the molten Al, stirring the molten to homogenate, keep the molten Al static for 20~30 minutes. Mix round well-proportioned before affusing.

3. Package and Storage:

Appearance: white metal nuggets.

250g/pc, 100pcs in a carton, 25kg/carton.

Storage: Keep dry and ventilated.

上海办 Shanghai Office

上海市浦东新区牡丹路 89 弄 4 号 602 室
R602,4#,89Nong, Mudan Road Pudong
Shanghai, China
Tel: 0086 21 6845 1592
Fax: 0086 21 6845 0923
fluorine@tatichem.com

...www.mintchem.com...

长沙办 Changsha Office

长沙市劳动西路 108 号长沙市化工研究所 HX 楼 707 室
HX707,108# Laodong Road West Changsha,
Hunan,China
Tel: 0086 731 85518147 8551 8261
Fax: 0086 731 8551 8167/ 8553 0767
fluorine@tatichem.com